



**VISUAL
MANAGEMENT
SYSTEMS**

**Standard
Bullet**



Indoor Cameras

- Medium Resolution 380 TVL
- 3.6MM lens
- Indoor installations in almost any location



I-888-308-CCTV WWW.VMSPDG.COM



VISUAL MANAGEMENT SYSTEMS



BB380

Indoor Cameras

MODEL	BB380
Image sensor	1/3" Super sensitive Color CCD
Effective Pixels	NTSC : 512(H)X492(V) PAL : 500(H)X582(V)
H.Resolution	380 TV Lines
Synchronizing system	Internal
Scanning system	NTSC 525 Lines PAL 625 Lines 2:1 Interlaced
Video output	1.0Vp-p Composite. 75 Ohms
S/N ratio	More than 50 dB (AGC Off)
Min. Illumination	0.5 Lux at F2.0
BLC	Automatic
White balance	Automatic
Gain Control	4dB ~ 30dB Auto
Gamma correction	$\gamma=0.45$
Smear Effect	0.005%
Shutter Speed	NTSC : 1/60i 1/100,000 sec PAL : 1/50i 1/100,000 sec
MTBF	80,000 hours
Power source	DC12V
Operating current	90mA w / regulated 12VDC in
Lens	Standard
	Option
Operating Temperature	14 °F 122 °F (-10 °C +50 °C)
Humidity	Within 90% RH
Output Terminal	4 Foot DIY cable with BNC-Female for Video, DC Jack-Male for Power
Measurement (mm)	21(D) x 80(L)
Weight (Approx.g)	210