



**VISUAL  
MANAGEMENT  
SYSTEMS**

**Standard  
Dome**

**D480**



**Indoor Cameras**

- 1/3" Sony Chipset - 480 TV lines
- 3.6MM Lenses
- Ideal for ceiling mounted, indoor locations



**I-888-308-CCTV WWW.VMSPDG.COM**



# VISUAL MANAGEMENT SYSTEMS



## D480

Indoor Cameras

MODEL		D480	
Image Format (1/3" Color CCD)		1/3" CCD, SONY High Resolution Super HAD CCD	
Effective Pixels		NTSC : 768(H)X494(V) PAL : 752(H)X582(V)	
H.Resolution		480 TV Lines	
Synchronizing system		Internal	
Scanning system		NTSC 525 Lines PAL 625 Lines 2:1 Interlaced	
Video output		1.0Vp-p Composite. 75 Ohms	
S/N ratio		More then 50 dB (AGC Off)	
Min. Illumination		0.5 Lux at F2.0	0.1 Lux at F2.0
BLC		Automatic	
Shutter Speed		NTSC : 1/60i/100,000 sec PAL : 1/50i/100,000 sec	
Gamma correction		γ=0.45	
White balance		2100K~8200K Auto	
Gain Control		4dB~30dB Auto	
Smear Effect		0.005%	
MTBF		80,000 hours	
Power source		DC12V (Tolerance:8V~15V)	
Operating current		130mA w / regulated power input	
Lens	Standard	3.6mm(92°)	
	Option	2.5mm, 2.9mm, 4.3 mm, 6.0mm, 8.0mm, 12mm, 16mm	
Operating Temperature		14° F ; 122° F (-10° C ; +50° C)	
Humidity		Within 90% RH	
Measurement (mm)		Refer to dimensions	
Weight (Approx.g)		400	
Output Terminal		2 Foot DIY cable with BNC-Female for Video, DC Jack-Male for Power	
Housing (Option)	Plastic wall mount bracket	Yes	Yes
	Weatherproof Metal Ceiling mount	Yes	Yes
	Weatherproof Metal wall mount	Yes	Yes